

ATF MULTI LV



AUTOMATIC LINE

Rev.5 of 05/2024

LEVELS OF QUALITY

The lubricant ULTRA ATF VI complies with the following international specifications:

- Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS), AW-1, AW-2
- PSA 16 350 560 80,
- Allison C-3 & C-4, TES-295, TES-389, TES-468
- American Motors ATF +3 (MS7176-E)
- ATF RED 1, RED 1K
- Audi/VW G 052 025 A2, G 053 025 A2, G 053 001, G 052 162 A1/A2, G 052 162 (ZF LifeguardFluid 5) (ZF No. S671 090 170), G 055 005 -A, -A1, -A2, -A6 (ZF LifeguardFluid 6) (ZF No. S671 090 255), G 055 162-A2, -A6 (ZF LifeguardFluid 6 Plus) (ZF No. S671 090 281), G 060 162 (ZF LifeguardFluid 8) (ZF No. S671 090 312), G 052 990, G 055 540 A2, G 052 533, 052 055
- Bentley P/N PY112995PA
- BMW JWS 3309 (T-IV), LA2634, LT71141 (ZF 5 HP 18FL/19FL/24A), ZF 5HP18FL, 5HP24, 5HP30, 7045E, ETL 8072B, ATF 2, ATF 3+, ATF 6, ATF 7
- BMW/Mini P/N 83 22 0 142 516, P/N 83 22 0 397 114, P/N 83 22 2 163 514 (BMW 8072 B); CAT TO-2; Chrysler ATF+, +2, +3 (MS7176E), +4; Chrysler/Dodge MOPAR AS 68 RC and AS 69 RC (T-IV), JWS 3309
- Chrysler/Dodge/Jeep 05127382AA, 68043742AA, 68157995AA, 68157995AB, Borg Warner 68049954AA, 68218925AA and 68218925AB, MOPAR SP IV, 68171866AA/68171869AA
- Daimler/Mercedes MB 236.12, 236.14, 236.41, 236.15, 236.16, 236.17, MB ZF 4HP20
- Daewoo LT 71141
- Daihatsu AMMIX ATF D-II, AMMIX ATF D-III SP
- Esso LT 71141
- FIAT T-IV type, JWS 3309; 9.55550-AV5, 9.55550-AV6
- Ford MERCON®, MERCON® LV (FF-WSS-M2C-938A/SF, XT-10 QLV), ATF C-ML5, FNR5 (Mazda M5, XT-9-QMM5), WSS M2C 138CJ, 166H, WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309; FORD/Lincoln/Mercury P/N XT-10-QLV [LV], P/N XT-6-QSP or -DSP [SP]GM 9986195 (Aisin AW-1, JWS 3309), TASA, DEXRON®-II, DEXRON®-IID, DEXRON®-IIE, DEXRON®-IIIG, DEXRON®-IIIH, DEXRON®-VI, 1940700, 1940767, 21005966, 22717466, 88900925, 9986195, 93160393, Transfer Case (AutoTrak II)
- Honda ATF-Z1 (except in CVTs), DW-1, Type 3.0, Type 3.1: 08263-999-01HE (EU), 08200-9017 (USA)
- GM/GMC/Opel/Saturn AW1, P/N 88863400, 88863401
- Hyundai/Kia SP-IV (00232-1904/04500-00115), SP-IV M (SP4-M), SPH-IV, SP-IV-RR, SP-III, Dex-II/ SP-II, JWS 3314, NWS 9638, 040000C90SG, NUMM040 CH20 Red-1
- Honda/Acura DW-1, Honda 082000-9017 (ATF Type 3.1)
- Hyundai/Kia NWS-9638 T-5, P/N 040000C90SG, SP-IV / SPH-IV
- Jaguar ATF 3403 M115, ATF 3403-M115, ATF LT71141, ZF 5HP24, JLM20238, ATF 3403 JLM20238, K17, JLM 20292, Fluid 8432, 02JDE26444, WSS-M2C922A1
- JASO M315-2013 1A, M315-2013 1A-LV, M315-2013 2A
- JEEP ATF+3
- KIA ATF SP-II, SP-III, SP-IV, SP-IVM, Red 1
- eMobility: Honda e:HEV; Honda iMMD; Mazda SKYACTIVE-HYBRID; Nissan Altima Hybrid; Tesla; Toyota THSII/Toyota Prius; Toyota THS 5th Gen.
- Land Rover TYK500050, LR0022460, LR023288
- Lexus JWS 3309
- MAN 339
- Mazda ATF D-II, ATF M-III, ATF M-V, ATF FZ, ATF A7, ATF F-1, ATF S-1, ATF N-1, ATF 3317, FW 6A EL, FW 6AX EL
- MINI COOPER T-IV
- Mitsubishi Diaqueen SK, SP-II, SP-III, SP-IV, AW, J2, J3, ATF-MA1, ATF PA; NAG 1 (Chrysler, Jeep, Cherokee)
- Nissan Matic Fluid C, D, J, K, P, S, W, Nissan/Infinity Matic-S
- Opel/GM 19 40 700, 19 40 767, 21005966 Transaxle, 22 17466, 88900925, 9986195
- Peugeot ZF 4HP20
- Peugeot/Citroen Z 000169756, (PSA) AL4 Automatic gearbox oil (#9730.AE)
- Porsche ZF 5HP19FL, ZF 5HP20, LT71141, ATF 3403-M115, T-IV (JWS 3309), 000 043 205 09, 999 917 547 00 (A2), 000 043 205 28, 000 043 304 00, Z 000169756
- PSA B71 2340
- Renault DPO/AL4
- Maserati P/N 231603
- Matic D2, Samsung SATF-D
- Saab T-IV (JWS 3309), 93 165 147 -AW-1, 93 160 393, Power Steering Fluid 2634, 45 30 09 800, 93160548
- Saturn T-IV (JWS 3309)
- Scion (all vehicles)
- Shell 3403, M115, 3353, 134, 1375.4, LA 2634, M-1375.4, L 12108
- Ssang yong DSIH 5M-66
- Subaru ATF, K0140Y0700, ATF 5AT, DEXRON®-II, ATF, ATF HP
- Opel Original ATF 09117946/93160393
- Suzuki ATF AW-1, AT OIL 5D06, ATF 2326, ATF 2384K, JWS 3309, ATF 3314, ATF 3317
- Texaco 7045-E, 8072B, N402
- Toyota ATF D-II, ATF D-III, ATF T-III, ATF T-IV, ATF WS, Toyota/Lexus/Scion WS
- Vickers M2950-S, I-286-S
- Voith 55.6335.xx (G607)
- Volvo 97325, 97335, CE 97340, PN 1161521, PN 1161540/1161640, PN 31256774/31256675, PN 1161621
- VW 5 HP (ZF 5 HP 30), 5HP (18FL, 30), 5HP (19FL, 24A), G-055-025 A2 (JWS 3309), G055 540 (A2), G 052 162 (ZF LifeguardFluid 5), G 055 005-A, -A2 (ZF LifeguardFluid 6), G 055 162-A2, -A6 (ZF LifeguardFluid 6 Plus), G 060 162 (ZF LifeguardFluid 8), TL 521 62; ZF all 3 & 4, ZF 6, ZF 8, ZF 9 speed transmissions, ZF TE-ML 05L, ZF TE-ML 09, ZF TE-ML 11A, 11B, ZF TE-ML 21L
- Service-fill for 8 and 9 speed step-Ats
- Dexron VI
- ZF-LIFEGUARDFLUID 6

PRODUCT DESCRIPTION

Duglas Oil ATF MULIT VI is a 100% SYNTHETIC fluid at low viscosity which is produced using carefully selected and balanced components and recommended for automatic transmissions, power steering, hydraulically assisted steering and torque converters, whenever it is required a product able to satisfy the requirements of GENERAL MOTORS Dexron VI.

It is especially recommended for automatic transmissions with a high number of gears and at the maximum performances for American, Asian and European Manufacturers.

APPLICATIONS

It ensures excellent performances in terms of:

- frictional properties;
- thermal-oxidative stability;
- wear and corrosion resistance;
- foaming resistance;
- compatibility with components for automatic transmissions, elastomer seals and plastic parts;
- extending oil change intervals;
- fuel economy.

Thanks to the above-mentioned features and to a high viscosity index it also ensures an excellent cold fluidity, by maintaining the desired viscosity at high temperatures.

TYPICAL FEATURES*

Density at 15°C Kg/dm ³	ASTM D1298	0,850
Colour		Red
Viscosity at 100°C cSt	ASTM D445	5,7
Viscosity Index	ASTM D2270	165
Flammability V.A. °C	ASTM D92	180
Pour Point °C	ASTM D97	-33

* The above-mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Sede Legale: Riviera di Chiaia, 256 - 80121 Napoli (NA)

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) – tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 16.000.000,00 int. vers.

info@ramoil.it – ramoil@pec.ramoil.it - www.ramoil.it